

MYPOOL

Peristaltic dosing pump with built in pH or Rx controller

The MyPool series of peristaltic dosing pumps are perfect for the domestic swimming pools, SPA and wellness centers. These pumps operate on the suction-compression created by rotors on a Santoprene® tube.

GENERAL FEATURES

- Proportional dosing mode.
- Flow rate up to 3 l/h.
- Pressure up to 3 bar.
- Possibility to measure to different types of electrochemical variables: pH or Rx.
- pH measurement range: 3 to 11 pH.
- Rx measurement range: +100 to +999 mV.
- Power supply: 230 V 50-60Hz.
- Maximum power consumption: 15w.
- Set point selection.
- Type of intervention (direct or inverse).
- Hysteresis.
- ON/OFF or proportional activation mode respect to the measure value.
- Delay time of the pump activation.
- Over dosing alarm, indicates an overdose situation.
- Relay output for signalled alarm status.
- Level switch input (included).
- Display: blue/white 16 digits.
- Supplied with complete installation kit:
 - pH or redox probe with 5m cable;
 - Saddle clamps;
 - PP probe holder ½ ";
 - Level probe;
 - Buffer solutions: pH 7 & 9 for pH version or 650 mV for redox version;
 - Injection valve (PVC/FPM);





TECHNICAL FEATURES

Version	Flow Rate l/h (US Gal/h)	Pressure bar (psi)
0101	1.5 (0.40)	1.5 (21)
0301	3 (0.79)	1.5 (21)
0202	2 (0.53)	2 (29)
0303	3 (0.79)	3 (43)

CODES

MyPool pH	Version
CXB4000301	0101
CXB4000401	0301
CXB4000501	0202
CXB4000601	0303

MyPool Rx	Version
CXB4000302	0101
CXB4000402	0301
CXB4000502	0202
CXB4000602	0303

MyPool No KIT	Version
CXB40003Z6	0101
CXB40004Z6	0301
CXB40005Z6	0202
CXB40006Z6	0303

DIMENSIONS (MM)

