

F & F-T SERIES

Compact peristaltic pumps with constant flow rate designed for discontinuous use

F series is a peristaltic pump with a constant flow rate for discontinuous use.

F-T series is a peristaltic pump with constant flow rate and an intergral timer (0-7 seconds; controlled by potentiometer) for discontinuous use.

GENERAL FEATURES

- Regolazione manuale della portata.
- Flow rate from 0.5 to 6 l/h.
- Maximum operating pressure 1 bar.
- Peristaltic tubing available in santoprene or silicone.
- Wall mounted with removable gearbox/motor for panel mounting.
- 230V power supply as standard.
- Optional 120V 12Vdc, 24Vac, 24Vdc power supplies (only available for certain models).
- Model 6 l/h only 24 Vdc.



DIMENSIONS (MM)



WATER TREATMENT KIT

FPM peristaltic pump accessories: made up of 2 m PE tubing (4x6mm), 2 m PP crystal tube (4x6mm), PP foot filter without check valve, PVC-FPM injection valve.



TECHNICAL FEATURES

Model	Flow Rate L7H	Max Pressure	Power Supply	RPM	Dimensions (in mm)		
					Height	Width	Depth
1	0.5	1	230V, 50/60 Hz	10	81	56	68
101	1.1	1	230V, 50/60 Hz	20	81	56	68
			240V, 50/60 Hz				
			110V, 50/60 Hz				
			24V, 50/60 Hz				
			24Vdc	22	81	56	68
12Vdc	21						
201	2.2	1	230V, 50/60 Hz	48	81	56	68
			240V, 50/60 Hz				
			110V, 50/60 Hz				
			24V, 50/60 Hz				
			24Vdc	50	81	56	80
12Vdc	60	81	56	80			
301	3.3	1	230V, 50/60 Hz	60	81	56	80
601	6	1	12/24Vdc	108	81	56	87

CODES

F Norprene	Version
PPF02 368 60	0001
PPF02 19260	0101
PPF 02 187 60	0201
PPF 02 331 60	0301
PPF 02 189 60	0601

F Santprene	Version
PPF02 368 64	0001
PPF02 19264	0101
PPF 02 187 64	0201
PPF 02 331 64	0301
PPF 02 189 64	0601

F-T Norprene	Version
PPF07 368 60	0001
PPF07 19260	0101
PPF 07 187 60	0201
PPF 07 331 60	0301
PPF 07 189 60	0601

F-T Santoprene	Version
PPF07 368 64	0001
PPF07 19264	0101
PPF 07 187 64	0201
PPF 07 331 64	0301
PPF 07 189 64	0601

F & FT SERIES

Peristaltic dosing pumps